

Model	Capacity (bushels)		Volume (ft ³)	Volume (m ³)	Diameter (feet)	Diameter (meter)	Height (feet)	Peak (meter)	Overall Height (feet)	Overall Height (meter)	M/TON Wheat	M/TON Corn	M/TON Rice
HTT18- 7	5,003	5,872	166	18'-0"	5.48	30'-2"	9.19	35'-5"	10.79	135	127	102	
HTT18- 8	5,576	6,543	185	18'-0"	5.48	32'-10"	10.00	38'-1"	11.60	151	142	113	
HTT18- 9	6,148	7,215	204	18'-0"	5.48	35'-6"	10.81	40'-9"	12.42	166	156	125	
HTT18-10	6,720	7,886	223	18'-0"	5.48	38'-2"	11.63	43'-5"	13.23	182	171	136	
HTT18-11	7,292	8,558	242	18'-0"	5.48	40'-10"	12.44	46'-1"	14.04	197	185	148	
HTT18-12	7,864	9,229	261	18'-0"	5.48	43'-6"	13.25	48'-9"	14.85	213	200	160	
HTT18-13	8,436	9,901	280	18'-0"	5.48	46'-2"	14.07	51'-5"	15.67	228	214	171	
HTT18-14	9,008	10,572	299	18'-0"	5.48	48'-10"	14.88	54'-1"	16.48	244	229	183	
HTT18-15	9,580	11,243	318	18'-0"	5.48	51'-6"	15.69	56'-9"	17.29	259	243	195	
HTT21- 9	8,590	10,081	286	21'-0"	6.40	37'-0"	11.27	43'-2"	13.15	233	218	174	
HTT21-10	9,369	10,995	311	21'-0"	6.40	39'-8"	12.08	45'-10"	13.96	254	238	190	
HTT21-11	10,148	11,909	337	21'-0"	6.40	42'-4"	12.90	48'-6"	14.78	275	258	206	
HTT21-12	10,926	12,823	363	21'-0"	6.40	45'-0"	13.71	51'-2"	15.59	296	277	222	
HTT21-13	11,705	13,737	389	21'-0"	6.40	47'-8"	14.52	53'-10"	16.40	317	297	238	
HTT21-14	12,484	14,651	415	21'-0"	6.40	50'-4"	15.34	56'-6"	17.22	338	317	254	
HTT21-15	13,262	15,565	441	21'-0"	6.40	53'-0"	16.15	59'-2"	18.03	359	337	269	
HTT24-12	14,562	17,089	484	24'-0"	7.31	46'-7"	14.19	53'-9"	16.38	394	370	296	
HTT24-13	15,579	18,283	518	24'-0"	7.31	48'-3"	14.70	56'-5"	17.19	422	396	316	
HTT24-14	16,596	19,477	552	24'-0"	7.31	51'-11"	15.82	59'-1"	18.00	449	421	337	
HTT24-15	17,613	20,670	585	24'-0"	7.31	54'-7"	16.63	61'-9"	18.82	477	447	358	
HTT24-16	18,630	21,864	619	24'-0"	7.31	57'-3"	17.44	64'-5"	19.63	505	473	378	
HTT24-17	19,647	23,058	653	24'-0"	7.31	59'-11"	18.26	67'-1"	20.44	532	499	399	
HTT24-18	20,664	24,251	687	24'-0"	7.31	62'-7"	19.07	69'-9"	21.25	560	525	420	
HTT27-12	18,450	21,652	613	27'-0"	8.23	46'-9"	14.24	54'-10"	16.71	500	468	375	
HTT27-13	19,737	23,163	656	27'-0"	8.23	49'-5"	15.06	57'-6"	17.52	534	501	401	
HTT27-14	21,024	24,674	699	27'-0"	8.23	52'-1"	15.87	60'-2"	18.33	569	534	427	
HTT27-15	22,311	26,184	742	27'-0"	8.23	54'-9"	16.68	62'-10"	19.15	604	566	453	
HTT27-16	23,599	27,695	784	27'-0"	8.23	57'-5"	17.50	65'-6"	19.96	639	599	479	
HTT27-17	24,886	29,206	827	27'-0"	8.23	60'-1"	18.31	68'-2"	20.77	674	632	505	
HTT27-18	26,173	30,717	870	27'-0"	8.23	62'-9"	19.12	70'-10"	21.58	709	664	532	
HTT27-19	27,461	32,227	913	27'-0"	8.23	65'-5"	19.93	73'-6"	22.40	744	697	558	
HTT30-12	23,184	27,208	771	30'-0"	9.14	48'-0"	14.62	57'-1"	17.39	628	589	471	
HTT30-13	24,773	29,073	823	30'-0"	9.14	50'-8"	15.44	59'-9"	18.21	671	629	503	
HTT30-14	26,362	30,938	876	30'-0"	9.14	53'-4"	16.25	62'-5"	19.02	714	669	535	
HTT30-15	27,951	32,803	929	30'-0"	9.14	56'-0"	17.06	65'-1"	19.83	757	710	568	
HTT30-16	29,541	34,668	982	30'-0"	9.14	58'-8"	17.88	67'-9"	20.64	800	750	600	
HTT30-17	31,130	36,533	1,035	30'-0"	9.14	61'-4"	18.69	70'-5"	21.46	843	790	632	
HTT30-18	32,719	38,399	1,088	30'-0"	9.14	64'-0"	19.50	73'-1"	22.27	886	831	665	
HTT30-19	34,308	40,264	1,140	30'-0"	9.14	66'-8"	20.31	75'-9"	23.08	929	871	697	
HTT33-12	28,544	33,499	949	33'-0"	10.06	49'-3"	15.01	59'-4"	18.08	773	725	580	
HTT33-13	30,467	35,755	1,013	33'-0"	10.06	51'-11"	15.82	62'-0"	18.89	825	773	619	
HTT33-14	32,390	38,012	1,077	33'-0"	10.06	54'-7"	16.63	64'-8"	19.70	877	822	658	
HTT33-15	34,313	40,269	1,140	33'-0"	10.06	57'-3"	17.47	67'-4"	20.52	929	871	697	
HTT33-16	36,236	42,526	1,204	33'-0"	10.06	59'-11"	18.26	70'-0"	21.33	981	920	736	
HTT33-17	38,159	44,782	1,268	33'-0"	10.06	62'-7"	19.07	72'-8"	22.14	1,033	969	775	
HTT33-18	40,082	47,039	1,332	33'-0"	10.06	65'-3"	19.88	75'-4"	22.96	1,085	1,018	814	
HTT33-19	42,005	49,296	1,396	33'-0"	10.06	67'-11"	20.70	78'-0"	23.77	1,138	1,066	853	
HTT36-12	34,555	40,553	1,149	36'-0"	10.97	50'-6"	15.39	61'-6"	18.74	936	877	702	
HTT36-13	36,843	43,238	1,225	36'-0"	10.97	53'-2"	16.20	64'-2"	19.55	998	935	748	
HTT36-14	39,132	45,924	1,301	36'-0"	10.97	55'-10"	17.01	66'-10"	20.36	1,060	993	795	
HTT36-15	41,420	48,610	1,377	36'-0"	10.97	58'-6"	17.82	69'-6"	21.18	1,122	1,052	841	
HTT36-16	43,709	51,296	1,453	36'-0"	10.97	61'-2"	18.64	72'-2"	21.99	1,184	1,110	888	
HTT36-17	45,997	53,981	1,529	36'-0"	10.97	63'-10"	19.45	74'-10"	22.80	1,246	1,168	934	
HTT36-18	48,286	56,667	1,605	36'-0"	10.97	66'-6"	20.26	77'-6"	23.62	1,308	1,226	981	
HTT36-19	50,574	59,353	1,681	36'-0"	10.97	69'-2"	21.08	80'-2"	24.43	1,370	1,284	1,027	



The bin is connected to the hopper cone via a rugged compression ring that ties the entire structure together securely. Note as well, the heavy-duty tie rod braces for added integrity and reliability. (ABOVE)

All MFS/York/Stormor hopper bins feature 14-inch outlets with standard rack and pinion gates for smooth operation. (BELOW)

